

NuPRO-E43


PICMG® 1.3 Full-Size LGA1151 Intel® Core™ i7/i5/i3 Processor-based SHB

Features

- 6th Gen Intel® Core™ i7/i5/i3 processor
- Intel® Q170 Express chipset supporting PCI Express 3.0
- Two DIMM socket support up to 32 GB DDR4 2133
- Four SATA 3.0 onboard with Intel Software RAID support
- Four COM ports (including RS-232/422/485)
- SEMA and SEMA Cloud support
- Intel PCIe slot bifurcation support



Product Illustration



Ordering Information

Modules

- **NuPRO-E43**
PICMG® 1.3 Full-Size LGA1151 Intel® Core™ i7/i5/i3
Processorbased SHB
Note: CPU, Memory module and Cooler kit are not included

Packing Lists

- NuPRO-E43
- 2x SATA data cable
- 1x 2 port USB 3.0 cable with bracket
- 1x 2 ports COM cable with bracket

Optional Accessories

- **TPM Module**
TPM module, Atmel AT97SC3204 TIS 1.2
- **DB-Audio 2**
DB-Audio 2, High definition audio daughter board with mic-in/line-in/line-out
- **1U CPU Cooler**
1U Thermal Module
- **2U CPU Cooler**
2U Thermal Module
- **3U CPU Cooler**
3U Thermal Module
- **PS/2 cable with bracket for keyboard/mouse**
- **DVI-D Cable with Bracket**
- **2 Port COM Cable with Bracket**
- **2 Port USB 3.0 right angle With Bracket**
- **1 Port COM Cable with Bracket**
- **Print Port Cable with Bracket**

Specifications

Processor System	
CPU	Intel® Core™ i7-6700, 3.4 GHz, 8M Cache, 14nm, 65W TDP, LGA1151 (4C/8T)
	Intel® Core™ i7-6700TE, 2.4 GHz 8M Cache, 14nm, 35W TDP, LGA1151 (4C/8T)
	Intel® Core™ i5-6500, 3.2 GHz, 6M Cache, 14nm, 65W TDP, LGA1151 (4C/4T)
	Intel® Core™ i5-6500TE, 2.3 GHz, 6M Cache, 14nm, 35W TDP, LGA1151 (4C/4T)
	Intel® Core™ i3-6100, 3.7 GHz, 3M Cache, 14nm, 51W TDP, LGA1151 (2C/4T)
	Intel® Core™ i3-6100TE, 2.7 GHz, 4M Cache, 14nm, 35W TDP, LGA1151 (2C/4T)
	Intel® Pentium® G4400, 3.3GHz, 3M Cache, 14nm, 54W TDP, LGA1151 (2C/2T)
	Intel® Pentium® G4400TE, 2.4GHz, 3M Cache, 14nm, 35W TDP, LGA1151 (2C/2T)
	Intel® Celeron® G3900, 2.8GHz, 2M Cache, 14nm, 51W TDP, LGA1151 (2C/2T)
	Intel® Celeron® G3900TE, 2.3GHz, 2M Cache, 14nm, 35W TDP, LGA1151 (2C/2T)
Chipset	Intel® Q170 Express Chipset
Memory	Dual-channel DDR4-2133 up to 32 GB
BIOS	AMI® UEFI BIOS 128 Mbit SPI Flash Memory
TPM	1x box header for TPM module (optional) Atmel AT97SC3204 TIS 1.2
Watchdog Timer	24~65535 sec. software programmable and can be generate system reset
Hardware Monitor	CPU voltage
	+3.3 V voltage
	+5 V voltage
	+12 V voltage
	CPU temperature
Operating Systems	CPU fan speed
	Microsoft® Windows® 7 32/64-bit
	Microsoft® Windows® 8.1 64-bit
	Microsoft® Windows® 10 64-bit Ubuntu 15.10
I/O Interfaces	
Serial ATA	4 x SATA 6.0 Gb/s connectors Software RAID support 0/1/5/10
Serial port	2x RS-232 via onboard 2.0 pitch box header 2x RS-232/422/485 with auto flow control via onboard 2.0 pitch box header
PCIe/PCI Bus (Via backplane)	1x PCIe x16 with Intel PCIe slot bifurcation support and can be configured to: 1x PClex 16 or 2x PCIe x8 or 1x PCIe x8 + 2x PCIe x4 to backplane (based on backplane) 1 x PCIe x4 to backplane 4 x PCI to backplane
USB	8x USB 3.0 (2 on rear I/O& 6 onboard box header) 4x USB 2.0 to backplane
LPT port	1x LPT port via onboard box header
Audio	1x box header for audio module DB-Audio2
KB/MS	1x pin header for PS/2 keyboard& Mouse
Audio	
Audio Codec	Realtek® ALC262 support by DB-Audio2 daughter board (optional)
Interface	Intel® High Definition Audio via onboard box header
Display	
Graphics	Integrated Intel® HD Graphics series, based on CPU for different GPU
VGA	1x VGA on rear I/O, resolution up to 1920 x 1200 @60Hz
DVI-D	1x DVI-D via onboard pin header, resolution up to 1920 x 1200@60Hz
Ethernet	
Controller	LAN1: Intel® I219LM PHY via RJ45 LAN2: Intel® I211-AT via RJ45
Interface	PCIe x1 bus
iAMT	Support on LAN1
Wake On LAN	Support on LAN1
Manageability	
SEMA	SEMA support with BMC, SEMA Cloud
Mechanical and Environmental	
Form Factor	Full-sized PICMG® 1.3 system Host Board
Dimensions	338 mm x 126 mm (L x W)
Operating Temp.	0°C to 60°C
Storage Temp.	-40°C to 80°C
Certifications	CE & FCC Class B
Relative Humidity	5% to 95%, non-condensing

*Extending operating temperature is optional and requires use of an industrial solid-state drive storage device or CFast card..

**Other Linux Distribution support by request



www.adlinktech.com

All products and company name listed are trademarks or trade names of their respective companies.
Updated Apr. 28, 2016. ©2016 ADLINK Technology, Inc. All Rights Reserved.
All specifications are subject to change without further notice.