

SP-KL Series

Intel® Core™ Processor-based Fanless
7"/10.1"/12.1"/15.6"/18.5"/21.5"
Panel Computer



Features

- Intel® Core™ i7-7600U/i5-7300U/i3-7100U processor
- 5 points capacitive or 1 point 5-wire resistive touch screen
- External I/O:
 - 1x DisplayPort, 1x USB 2.0, 1x USB 3.0, 2x GbE ports
 - 2x COM port(RS-232/422/485)
- Internal I/O:
 - 1x mPCIe slot, 1x USIM slot, 1x USB 2.0, 2x I2C, 1x 8 GPIO
 - 1x DisplayPort
 - 1x keypad port to support 32 physical key
 - 1x port for volume and display backlight adjustment
- Expansion I/O:
 - Customized specifically by FM board
- Storage options: 1x eMMC, 1x SATA, 1x Micro SD, 1x M.2
- Built-in ADLINK SEMA management solution
- 2x 2W speaker, 1x Mic in/Line out, 1x buzzer
- Front side IP65 protection
- 1x eSIM (optional)

Software Support

- Windows® 10, Linux

Starter Kit

- 15.6" Smart Panel, 4GB DDR3L, 32GB SSD, function module board, internal cable set, and holders

Optional Accessories

- Memory
Upgrade to 2/4/8 GB DDR3L memory
- Storage
2.5" HDD/SSD, M.2 SSD, Micro SD
- Adapter
12V 60W, 12V 84W power adapter
- I/O Cables
Keypad, power reset, audio, and USB cables
- Wireless Communication Kit
Wi-Fi/BT/4G LTE wireless kit

Ordering Information

- SP-07WP-KL Series
7" smart panel computer
- SP-10WP-KL Series
10.1" smart panel computer
- SP-12WP-KL Series (Optional)
12.1" smart panel computer
- SP-15WP-KL Series
15.6" smart panel computer
- SP-18WP-KL Series (Optional)
18.5" smart panel computer
- SP-21WP-KL Series
21.5" smart panel computer

Specifications



Smart Panel - KL Series						
Model Name	SP-07WP-KL	SP-10WP-KL Series	SP-12WP-KL (Optional)	SP-15WP-KL	SP-18WP-KL (Optional)	SP-21WP-KL
System						
Processor	Intel® Core™ i3-7100U 2.4 GHz/ Intel® Core™ i5-7300U 2.6/3.5 GHz/ Intel® Core™ i7-7600U 2.8/3.9 GHz (Turbo) 15W					
Memory	1x SODIMM non-ECC 1867/1600 MHz DDR3L memory up to 8GB					
Storage	1x SATA 6 Gbps port/ 1x M.2 SATA 6 Gbps port, M key 2280/ 1x Micro SD card eMMC 5.0, Up to 64GB (Optional)					
External I/O						
Ethernet	2x GbE (Standard: Intel® I211-AT, Option: Intel® I210IT), RJ-45, WOL					
Serial Port	2x RS-232/422/485 programmable, support 9 bit mode and auto flow					
USB 2.0	1x USB 2.0, Type A, OCP, 1000mA					
USB 3.0	1x USB 3.0, Type A, OCP, 1600mA					
DP	1x DP, DP++, supports resolutions up to 4096 x 2160					
Internal I/O						
Mini PCIe	1x full size mPCIe, integrated PCIe and USB interface					
PCIe	1x PCIe4 edge connector on PCB					
DisplayPort	1x DP, DP++, supports resolutions up to 4096 x 2160					
SIM	1x SIM slot or 1x eSIM (optional) for 3G/4G communication					
USB 2.0	1x wafer for USB 2.0 clients					
I ² C	1x wafer, supports IoT sensors (not including algorithm), 1x wafer for I ² C clients					
Audio	1x wafer for 2x 2W stereo speaker, built-in amplifier 1x wafer for Mic-in and Line-out 1x wafer for buzzer					
Keys	1 box header for 32 physical keys (Optional) 1 wafer, supports LCD backlight up/down, volume up/down (Optional)					
GPIO	1 x wafer, supports 8-pin GPIO					
Power						
Connector	1x 4-pin power connector AT/ATX					
DC Input	12V ± 5% / 9-36V, both with OVP/UVp protection					
Power/Fail Reset	1x wafer, support system reset & power button and power LED					
Backup Battery	1x wafer for UPS kit to backup data when AC shuts down (Optional)					
Notification						
Thermal Sensors	1x CPU Tj, 2x PCBA top & bottom-mounted thermal sensors (Optional)					
TPM	TPM 2.0 (Optional)					
LED Indicator	1x wafer for 10 LED indicators (4x COM port Tx/Rx, 1x Watch Dog Timer, 3x user defined)					
Debug Port	1x 40-pin multipurpose flat cable connector for use in combination with DB-40 debug port					
Mechanical Bracket						
IP Grade	IP65 for front					
Material	SGCC					
Display Component Specification						
	7"	10.1"	12.1"	15.6"	18.5"	21.5"
Display Ratio	16:9	16:10	16:10	16:9	16:9	16:9
Display Resolution	1024 x 600	1280 x 800	1280 x 800	1366 x 768	1366 x 768	1920 x 1080
Display View Angle	85/85/85/85	85/85/85/85	89/89/89/89	85/85/80/80	85/85/80/80	60/60/70/70
Luminance (Nits)	600 cd/m ²	500 nits (typ)	400 nits (typ)	450 nits (typ)	450 nits (typ)	400 nits (typ)
Touch Screen	5 points capacitive touch screen 1 point 5 wire resistive touch screen (Optional)					
Environmental						
Operating Temperature	-20 to 60°C	-20 to 70°C	-20 to 70°C	0 to 50°C	0 to 50°C	0 to 40°C
Storage Temperature	-20 to 70°C			-20 to 60°C		
Operating Humidity	10-90% RH operating, non-condensing, 5-95% RH storage					
Vibration	OP 5 Grms, 5-500Hz (with SSD), EN61373 Class 1B (Railway Reliability), ISO 7637-2					
ESD	Air: ±15kV, Contact: ±8kV					
Software						
SEMA	SEMA 3.5					
WDT	Watch Dog Timer supported					
Operating System	Windows® 10 IOT Enterprise x64 bit, Linux Ubuntu 16.04 LTS, QT compatible, 64 bit					

